# sartorius

## Pre-heated Quartz Microfiber Filters Grade Q3400



turning science into solutions



### Description

The quartz microfiber material of the Sartorius pre-heated filters, grade Q3400, is made of high-purity quartz microfibers without any addition of glass microfibers or binding agents. In addition, the Q3400 filter grade is tempered to remove all chemically combined water and to give the filters excellent weight and dimensional stability. Sartorius filters are especially suitable for emissions monitoring at temperatures of up to 900°C and wherever filters of the highest purity are needed. These quartz microfiber filters are even purer than glass microfiber filters.

#### Applications

- Emissions monitoring at high temperatures
- Air pollution monitoring (US EPA PM 10\*)
- Analysis of hot and acidic gases
- Trace metal element analysis
- Analytical and gravimetric analyses
- Analysis of dust levels according to EN 13284 1:2001

\*US EPA PM 10: United States Environmental Protection Agency – Particulate Matter, Level 10



#### **Specifications**

Material	100% high-purity quartz, binder-free, tempered
Basis weight	85 g/m <sup>2</sup>
Thickness	0.43 mm
Penetration, 0.3 μm 15 cm/s using paraffin oil (EN 143)	<0.002 %
Efficiency, 0.3 μm 15 cm/s using paraffin oil (EN 143)	99.998 %
Temperature resistance	Up to 900°C

#### **Ordering Information**

Order Number	$\varnothing$ in mm	Qty. per Box
Q340025G	25	25
Q340037G	37	25
Q340045G	45	25
Q340047G	47	25
Q340050G	50	25
Q340082N	82	100
Q340090N	90	100

Other diameters or formats are available on request.

Sartorius Stedim Biotech GmbH August-Spindler-Strasse 11 37079 Goettingen, Germany

Phone +49.551.308.0 Fax +49.551.308.3289

Specifications subject to change without notice. Printed and copyrighted by Sartorius Stedim Biotech GmbH. | W Publication No.: SL-1109-e140702 Order No.: 85037-544-65 Ver. 07 | 2014

